DIE CAST MACHINERY LLC

3246 West Monroe Street
Waukegan, IL 60085-3029 USA
1-847-360-9170 Phone
www.diecastmachinery.com

Die Cast Machinery, LLC Inventory number: DCM-6076

Used Die Pro Model: Core Cool 3.1.5 Dual (two) Zone Portable Refrigerated Water Chiller Temperature Control Unit

Status:	**Sold**
Manufacturer:	Die Pro
Model:	Core Cool 3.1.5
ID Number:	DCM-6076

Die Pro - Core Cool 3.1.5 Dual (two) Zone Portable Refrigerated Water Chiller Temperature Control Unit, Allen-Bradley PLC/Touch Panel Controls

View this machine online: DCM-6076



Specifications

	U.S. Standard	Metric
Main Cooling Power (Zone #1-4):		
Pump Motor Size (Zone #1-4):		
Flow Rate (Zone #1-4):		
Connection size/type (Zone #1-4):		
Maximum Operating Temperature:		
Power Requirements:	480 volt / 3 phase / 60 cycle	480 volt / 3 phase / 60 cycle
Overall Size (L x W x H):		
Weight:		

Features & Accessories:

- NEW IN 2022
- ALLEN BRADLEY COMPACT LOGIX CONTROL SYSTEM
- COOLING PUMP OUTPUT RATING IN P.S.I. (BAR) – 300 (20).
- NETWORK COMMUNICATION PROTOCOLS. (ETHERNET/IP, PROFINET, PROFIBUS, CC LINK, MODBUS, DEVICENET, DH+, SERIAL) VIA GATEWAY MODULE
- NEMA TYPE POWER CONTROL CABINET FOR OPERATION WITH INPUT VOLTAGE 480 VOLT 60 Hz 3 PHASE.
- 316 SS PIPE FITTINGS.
- COOLING SYSTEM TANK CAPACITY. (52.5 GALLONS) (198.7 LITERS)

Terms of Sale:

Price: sold

Shipping Terms: Ex-works

Questions? Call (847) 360-9170 and mention DCM-6076.

DIE CAST MACHINERY LLC

3246 West Monroe Street
Waukegan, IL 60085-3029 USA
1-847-360-9170 Phone
www.diecastmachinery.com

Photos - DCM-6076

Click any photo to open it full size on our website.



Photo 1 of DCM-6076 - view online



Photo 2 of DCM-6076 - view online



Photo 3 of DCM-6076 - view online




Photo 4 of DCM-6076 - view online

Description:

Used, Die Pro Model Core Cool 3.1.5 Dual (two) Zone Portable Refrigerated Water Chiller Temperature Control Unit For_Sale, Features Include: ALLEN BRADLEY COMPACT LOGIX CONTROL SYSTEM, COOLING PUMP OUTPUT RATING IN P.S.I. (BAR) – 300 (20)., NETWORK COMMUNICATION PROTOCOLS. (ETHERNET/IP, PROFINET, PROFIBUS, CC LINK, MODBUS, DEVICENET, DH+, SERIAL) VIA GATEWAY MODULE, NEMA TYPE POWER CONTROL CABINET FOR OPERATION WITH INPUT VOLTAGE 480 VOLT 60 Hz 3 PHASE., 316 SS PIPE FITTINGS., COOLING SYSTEM TANK CAPACITY. (52.5 GALLONS) (198.7 LITERS), Allen-Bradley PLC/Touch Panel controls, second Hand, DCM-6076

PURCHASER'S (Buyer's) RESPONSIBILITY AND INDEMNITY: Used machines, equipment or any part thereof, may not incorporate approved activating mechanisms, operator safety devices or safety guards as required by OSHA or otherwise. It shall be a Purchaser's (Buyer's) responsibility to ensure that any and all merchandise or equipment purchased from Die Cast Machinery, LLC or its affiliates is installed and operated in a proper and safe manner. Purchaser (Buyer) also acknowledges that it may have to install or change guards, safeties, warnings or other components to ensure that the merchandise or machines purchased will conform to all laws, codes, regulations, ordinances, statutes, insurance requirements and industry standards. Purchaser agrees to defend, indemnify and hold harmless Die Cast Machinery, LLC from and against all suits, claims, costs, damages and expenses, including, but not limited to, reasonable attorneys' fees,

3246 West Monroe Street
Waukegan, IL 60085-3029 USA
1-847-360-9170 Phone
www.diecastmachinery.com

arising out of, or in connection with, the transportation, purchase, ownership, or use of the merchandise or equipment sold hereunder. Information has been obtained from sources deemed reliable, buyers should avail themselves of the opportunity to inspect the items before purchase.